

Specification Sheet

Part Number: 170-03101

Resists gasoline and engine chemicals.

Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Expands up to 150% for economical and expeditious installation.

Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.

Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.



Plenum Rated Expandable Braided Sleeving (Halar), 0.25" Dia, White, 200 ft/reel

Article Number 170-03101

Type BSHLR1410

Color White (WH)

Quantity Per reel

Product Description

Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern. This sleeving is made from strands of high temperature, flame resistant Halar monofilaments that are able to resist a wide range of corrosive chemicals and organic solvents. Its low flame spread and smoke generation properties make it the perfect option for use in technologically advanced applications, such as those in the automotive, aerospace and vital military markets.

Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 0.25" Dia, White, 200 ft/reel		
Global Part Name	BSHLR1410-E/CTFE-WH		
Length L (Imperial)	200.0		
Length L (Metric)	61.0		
Bundle Diameter Min (Imperial)	0.125		
Bundle Diameter Min (Metric)	3.2		
Bundle Diameter Max (Imperial)	0.437		
Bundle Diameter Max (Metric)	11.1		
Diameter D (Imperial)	0.25		
Diameter D (Metric)	6.4		
Nominal Diameter (Imperial)	0.25		
Nominal Diameter (Metric)	6.4		
Material	Ethylene Chlorotrifluoroethylene (E/CTFE)		
matorial	Earytonic Officioninaciocarytonic (E/OTT E)		

E/CTFE

Material Shortcut

Flammability UL VW-1 FAR 25

Halogen Free No

UV Resistant (Yes/No) No

Operating Temperature -103°F to +302°F (-75°C to +150°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Certification/Specification UL 2024 UL | UL 746A UL | ANSI/UL 746B UL | UL 1441

UL Recognized (US) Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 60.96

Customs Number 5808100000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).