

# Power Cord C14 to C15 - Heavy-Duty, 15A, 250V, 14 AWG, 3 ft. (0.91 m), White

# MODEL NUMBER: P018-003-AWH











# **Highlights**

- Easy-to-identify white SJT jacket and fully molded white ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

# **Package Includes**

 P018-003-AWH Heavy-Duty Computer Power Cord, White, 3 ft.

Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

#### **Features**

## Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- · Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

## **Color-Coded Cable and Connectors**

• Colored white for easy identification in crowded rack or workstation

# **Optimum Construction**

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating
- UL-listed

# **Specifications**

OVERVIEW	
UPC Code	037332199140
Device Compatibility	Network Switch; UPS; PDU
Country/Region	North America



INPUT		
Maximum Input Amps	15	
Voltage Compatibility (VAC)	100-250	
PHYSICAL		
Plug Color	White	
Cable Jacket Color	White	
Cable Jacket Material	PVC	
Cable Jacket Rating	FT2	
Power Cord Jacket Type	SJT	
Cable Outer Diameter (OD)	9.2mm	
Number of Conductors	3	
Wire Gauge (AWG)	14	
Wire Gauge (OD - mm²)	2.08	
Cable Length (ft.)	3	
Cable Length (m)	0.91	
Cable Length (cm)	91.44	
Shipping Dimensions (hwd / in.)	9.90 x 7.00 x 0.50	
Shipping Dimensions (hwd / cm)	25.15 x 17.78 x 1.27	
Shipping Weight (lbs.)	0.44	
Shipping Weight (kg)	0.20	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
Operating Humidity Range	20% to 80% RH	
Storage Humidity Range	20% to 80% RH	
CONNECTIONS		
Side A - Connector 1	IEC-320-C14	
Side B - Connector 1	IEC-320-C15	
FEATURES & SPECIFICATIONS		
Antibacterial	No	
Angled Plug	No	
High Voltage	Yes	



Locking Plug	No	
Coiled Power Cord	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.