

Power Extension Cord/Splitter, NEMA L6-30P to 2x NEMA L6-30R Y Splitter, Heavy-Duty - 30A, 250V, 10 AWG, 1 ft. (0.31 m), Black

MODEL NUMBER: P041-001-2









L6-30P to L6-30R splitter allows two devices with NEMA L6-30P plugs to share one AC power input cord and one NEMA L6-30R outlet.

Features

Heavy-Duty Y-Style Splitter Cable Connects 2 Devices with L6-30P Plugs to One AC OutletThis Y splitter cable features 10 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. With this extension cord splitter, a single NEMA L6-30R outlet can power two devices, such as PDUs, UPS systems, instrument amplifiers and other equipment compatible with a NEMA L6-30P plug. Ideal for areas where AC outlets are limited, such as rack cabinets or small network closets, this L6-30P to L6-30R Y splitter is compatible with Tripp Lite power and extension cords. The 1-ft. (0.31 m) length helps reduce cable clutter.

Locking Connectors Help Prevent Accidental Disconnection and Expensive Downtime Having a cable come loose accidentally can mean the loss of power and costly downtime. Locking connectors on each end help you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering dual PDUs, UPS systems or other heavy-duty devices
- Adds 1-ft. (0.31 m) to your existing power connection to provide flexibility in placing devices
- Locking connectors maintain secure link to avoid loss of power and costly downtime
- Thick 10 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect 2 devices like PDUs and UPS systems to one power outlet up to 1-ft. (0.31 m) away in your office or work space
- Save space in a 0U vertical rack-mount PDU by plugging two rack devices into one outlet
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P041-001-2 L6-30P to 2x L6-30R Y Splitter, 1-ft. (0.31 m), Black

Specifications

| OVERVIEW | |
|----------------------|--|
| UPC Code | 037332141484 |
| Device Compatibility | Server; Router; Network Switch; UPS; PDU |
| Country/Region | North America |
| INPUT | |
| Maximum Input Amps | 30 |



| Voltage Compatibility (VAC) | 100-250 | |
|--|---------------------------|--|
| | | |
| PHYSICAL | | |
| Plug Color | Black | |
| Cable Jacket Color | Black | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | FT2 | |
| Power Cord Jacket Type | SJT | |
| Cable Outer Diameter (OD) | 14.5mm | |
| Number of Conductors | 3 | |
| Wire Gauge (AWG) | 10 | |
| Wire Gauge (OD - mm²) | 5.26 | |
| Cable Length (ft.) | 1 | |
| Cable Length (m) | 0.30 | |
| Shipping Dimensions (hwd / in.) | 15.80 x 11.80 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 40.13 x 29.97 x 1.27 | |
| Shipping Weight (lbs.) | 2.40 | |
| Shipping Weight (kg) | 1.09 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4 to 140 F (-20 to 60 C) | |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) | |
| Operating Humidity Range | 20% to 70% RH | |
| Storage Humidity Range | 20% to 80% RH | |
| CONNECTIONS | | |
| Side A - Connector 1 | NEMA L6-30P | |
| Side B - Connector 1 | (2) NEMA L6-30R | |
| FEATURES & SPECIFICATIONS | | |
| Angled Plug | No | |
| High Voltage | Yes | |
| Locking Plug | Yes | |
| | | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.