

3U UPS Replacement 72VDC Battery Cartridge (1 Set of 6) for Select SmartOnline UPS

MODEL NUMBER: RBC96-3U



Highlights

- Certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leakproof construction
- Maintenance free
- Wide operating temperature range

Package Includes

 One pre-assembled battery pack consisting of six 12V batteries

Description

Premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See the UPS replacement battery web page to confirm compatibility and quantity required.

COMPATIBLE WITH SU3000RTXL3U, SU3000RTXR3U, SU3000XL (versions with pre-assembled six-battery cartridges only; see compatiblity listing for non-assembled battery versions).

Features

- Restores UPS runtime performance to original specifications
- Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

Specifications

| OVEDVIEW. | |
|--------------------------|---|
| OVERVIEW | |
| UPC Code | 037332126153 |
| BATTERY | |
| DC System Voltage (VDC) | 72 |
| Included Battery Set | Contains (6) 12V 9AH sealed lead acid batteries |
| Typical Battery Lifespan | 3 to 5 years, depending on UPS operating conditions |
| PHYSICAL | |
| Rack Height | 3U |



| Minimum Required Rack Depth (cm) | 48.26 |
|---|---------------------------|
| Minimum Required Rack Depth (inches) | 19 |
| Shipping Dimensions (hwd / in.) | 5.20 x 13.50 x 8.10 |
| Shipping Dimensions (hwd / cm) | 13.21 x 34.29 x 20.57 |
| Shipping Weight (lbs.) | 38.73 |
| Shipping Weight (kg) | 17.57 |
| Unit Dimensions (hwd / in.) | 4.000 x 6.000 x 15.500 |
| Unit Dimensions (hwd / cm) | 10.2 x 39.4 x 15.2 |
| Unit Weight (lbs.) | 37.0 |
| Unit Weight (kg) | 16.78 |
| ENVIRONMENTAL | |
| Relative Humidity | 0-95% non-condensing |
| Operating Elevation (ft.) | 10,000 ft. |
| Storage Elevation (ft.) | 10,000 ft. |
| Operating Elevation (m) | 3,000 m |
| Storage Elevation (m) | 3000 m |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (U.S. & Canada) | 18-month limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.