

7-Port Portable USB 3.0 SuperSpeed Mini Hub, Aluminum

MODEL NUMBER: U360-007-AL











Connects to the USB 3.0 port on your laptop, Ultrabook or computer to give you 7 external USB 3.0 ports.

Description

The U360-007-AL 7-Port Portable USB 3.0 SuperSpeed Mini Hub's built-in USB cable connects to your laptop, Ultrabook or computer to provide seven available USB 3.0 ports. Just plug and play with no drivers or software needed. The included external power supply provides 5V 3A to be shared among all seven USB ports, with each port capable of providing up to 1.5A for fast charging of mobile devices. All seven ports support USB Battery Charging (BC) specification v1.2.

This portable hub supports USB 3.0 data transfer rates up to 5 Gbps—ten times faster than USB 2.0—and is backward compatible with USB 2.0 and USB 1.1 devices. The compact, lightweight aluminum case fits easily into your pocket, backpack, briefcase or laptop bag.

Features

Increases Your Computer's USB 3.0 Ports from 1 to 7Expands your laptop, Ultrabook or computer's USB 3.0 port to 7 external USB 3.0 portslncluded external power supply provides 5V 3A to be shared among all portsEach port is capable of providing up to 1.5ASupports USB Battery Charging (BC) specification v1.2

Excellent Speed and Versatile PerformanceSupports USB 3.0 data transfer rates up to 5 Gbps—10 times faster than USB 2.0Backward compatible with USB 2.0 and USB 1.1

Take the Hub AnywhereCompact case made from lightweight aluminumFits easily into your pocket, backpack, briefcase or laptop bagBuilt-in cable is perfect for travel

Specifications

OVERVIEW	
UPC Code	037332201027
Product Type	Hub
Technology	USB 3.x

Highlights

- USB ports can provide up to 1.5A for charging mobile devices*
- All seven ports support USB Battery Charging (BC) specification v1.2
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Plug and play—no drivers or software needed
- Fits easily into pocket, backpack, briefcase or laptop bag
- Backward compatible with USB 2.0 and USB 1.1
- *When using the included external power supply

System Requirements

 Device with USB port (USB 3.0 port needed to achieve USB 3.0 speeds)

Package Includes

- U360-007-AL 7-Port Portable USB 3.0 SuperSpeed Mini Hub
- External power supply (Input: 100–240V, 50/60 Hz, 0.6A; Output: 5V 3A)



Host Connector	USB A (MALE)	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
VIDEO		
Number of Monitors Supported	0	
DATA		
Data Ports	(7) USB A (FEMALE)	
Data Ports Details	(7) USB-A - USB 3.2 Gen 1 (5 Gbps)	
INPUT		
AC Power Adapter Plug(s)	NEMA 1-15P North America	
AC Power Adapter Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.6A	
AC Power Adapter Output Specs (V / A)	5V / 3A	
AC Power Adapter Cord Length (ft.)	5	
AC Power Adapter Cord Length (m)	1.5	
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
Bus Powered	No	
Product Length (in.)	21.6	
Product Length (cm.)	54.86	
Product Length (ft.)	1.8	
Product Length (m.)	0.548	
POWER		
Power Source Type	AC Adapter	
AC Adapter	Input: 100-240V, 50/60Hz, 0.6A; Output: 5V, 3A	
DC Barrel Plug	OD: 3.5 x 1.35 x 10mm, Positive Pin, Negative Sleeve	
Power Consumption (Watts)	1.4	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	White when connected and powered	
CHARGING		
Charging Ports	USB-A: 5V 1.5A (7.5W)	
Charging Ports Details	All seven ports support USB Battery Charging v1.2	
Charging Ports / Amps	(7) 1.5A	
PHYSICAL		



Color	Black	
Material of Construction	Aluminum	
Cable Jacket Material	TPE	
Cable Jacket Rating	VW-1	
Shipping Dimensions (hwd / in.)	2.20 x 4.40 x 7.70	
Shipping Dimensions (hwd / cm)	5.59 x 11.18 x 19.56	
Shipping Weight (lbs.)	0.87	
Shipping Weight (kg)	0.39	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Packaging Type	Box	
Unit Weight (lbs.)	0.53	
Unit Weight (kg)	0.24	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 158°F (-20° to 70°C)	
Storage Temperature Range	14° to 158°F (-10° to 70°C)	
Relative Humidity	10% to 90% RH, Non-Condensing	
BTUs	4.7 BTU/Hr	
Power Provided to Connected Device(s)	5V 1.5A (7.5W) Output per USB Port	
CONNECTIONS		
Number of Ports	7	
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	(7) USB 3.0 A (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
STANDARDS & COMPLIANCE		
External Power Supply Certifications	CE; FCC; UL; cUL; TUV; CCC; RoHS	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.