

4-Port USB-C Hub, USB-C to 4x USB-A Ports, USB 3.0. Silver

MODEL NUMBER: U460-004-4A











Adds USB-A ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

Description

The U460-004-4A USB 3.1 Gen 1 USB-C Portable Hub expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for adding a thumb drive and other USB peripherals and charging mobile devices—all at the same time.

The plug-and-play U460-004-4A requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Four USB-A ports accept USB peripherals, such as a flash drive, mouse, keyboard or printer. Each port supports up to 5V/1.5A (7.5W) for fast charging of mobile devices. They also support fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices. A USB Micro-B port connects to an optional external USB power adapter to provide the hub with additional power if needed.

Features

Turn Your Device's USB-C Port into a Workstation

- Ideal for adding USB peripherals and powering and charging a mobile device simultaneously
- Plug-and-play operation with no software, drivers or external power required
- Lightweight aluminum housing about the size of a credit card for easy carrying in a pocket, purse or laptop bag

Connect USB Peripherals

- 4 USB-A ports accept flash drives, mice, keyboards, printers and other USB peripherals
- Supports up to 5V/1.5A (7.5W) for fast charging of mobile devices
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1

Note: Host must support USB OTG (On-the-Go)

Extra Port for Extra Power

 USB Micro-B port connects to optional external power adapter to provide hub with additional power if needed

Highlights

- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- USB-A ports provide up to 1.5A each for charging devices
- USB Micro-B port connects to optional adapter for extra power
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required

System Requirements

 Source device with USB-C or Thunderbolt 3 port

Package Includes

 U460-004-4A USB 3.1 Gen 1 USB-C Portable Hub



Built-In Cable with Reversible USB-C Connector

• Fumble-free reversible USB-C plug connects in either direction for quick connection every time

Specifications

-		
OVERVIEW		
UPC Code	037332190208	
Product Type	Hub	
Host Connector	USB C (MALE)	
VIDEO		
Number of Monitors Supported	0	
Extended Mode	No	
Mirror Mode	No	
DATA		
Data Ports	(4) USB A (FEMALE)	
Data Ports Details	(4) USB-A - USB 3.2 Gen 1 (5 Gbps)	
INPUT		
Bus Powered	Yes	
Product Length (in.)	14.4	
Product Length (cm.)	36.58	
Product Length (ft.)	1.2	
Product Length (m.)	0.37	
BATTERY		
Battery Charging (5V/1.5A Port)	Yes	
POWER		
Power Consumption (Watts)	0.7	
CHARGING		
Total Charging Watts	7.5	
Charging Ports	USB-A: 5V 1.5A (7.5W)	
Charging Ports / Amps	(4) 1.5A	
PHYSICAL		



Color	Silver	
Material of Construction	Aluminum	
Cable Jacket Rating	VW-1	
Shipping Dimensions (hwd / in.)	1.20 x 4.90 x 3.90	
Shipping Dimensions (hwd / cm)	3.05 x 12.45 x 9.91	
Shipping Weight (lbs.)	0.22	
Shipping Weight (kg)	0.10	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Packaging Type	Box	
Unit Weight (lbs.)	0.16	
Unit Weight (kg)	0.07	
ENVIRONMENTAL		
Operating Temperature Range	32° to 122°F (0° to 50°C)	
Storage Temperature Range	14° to 167°F (-10° to 75°C)	
Relative Humidity	0% to 85% RH, Non-Condensing	
BTUs	2.4 BTU/Hr	
Power Provided to Connected Device(s)	Up to 5V 1.5A (7.5W) per USB Port	
CONNECTIONS		
Number of Ports	5	
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	(4) USB 3.0 A (FEMALE)	
Side B - Connector 2	MICRO-USB B (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
UASP Support	No	
Auto MDIX Support	No	
Full Duplex Support	No	
Suspend Mode Support	No	
Remote Wakeup Support	No	
Driver Required	No	
STANDARDS & COMPLIANCE		



Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.