

Zero Smog 6V 100-120 Volt

Product no.: T0053666299N



Benefits

- › Equipped with HEPA H13 particle filter and Fine dust pre-filter F7
- › The Constant Flow Control (CFC) guarantees optimal air flow regulation for each working place independent of the connected workplaces
- › 3 operating modes: Standard Speed Control: Selected by the user irrespective of the load on the system, Speed Limiting Control: The speed is automatically varied to match the load on the system, Economy Control: The rate of fume absorption is maintained at a constant value
- › Electronic filter control with optical and acoustical filter alarm
- › Low noise emission levels for a quiet workspace
- › RS232 port, can be remotely controlled via remote control (optional accessory) or by a PC with RS232 connection
- › Max. blower capacity 615 m³/h
- › Efficiency test via USB port



Technical Data

Dimensions L x W x H (mm)	460 x 460 x 665
Dimensions L x W x H (inches)	18,11x18,11x26,18
Weight (approx.) in kg	40
Voltage	120 V, 60 Hz
Power	460 VA
Noise level (distance 1 m) dB(A)	< 51
Max. vacuum	2800 Pa
Capacity m³/h	615
Pre-filter	T0058735836
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon / 50 % Chemisorb)
Max. capacity	1–8 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	The USB port can be used to load firmware updates, run efficiency tests and logdat data.
WX-compatible	on